

*Rely on us.*SM

Varn® Enviroflex Solwash

The ultimate in powerful flexo/gravure cleaning

Cleaner for Flexographic applications

Product Features

- Varn® Enviroflex Solwash is a blend of extremely powerful ink removing solvents specially formulated for the easy removal of solvent based inks and coatings.
- Varn® Enviroflex Solwash is designed to thoroughly deep clean and rejuvenate anilox rollers either on or off the press, optimising anilox roller life and press performance.
- Varn® Enviroflex Solwash is recommended for use diluted as part of a daily cleaning schedule to assist in maintaining press performance and print quality or for use undiluted as part of a weekly or monthly deep cleaning schedule and rejuvenation of anilox rollers on or off press.

Advantages of Varn® Enviroflex Solwash

- Very strong solvency.
- Effective removal of solvent inks and coatings.
- Suitable for regular deep and thorough cleaning maintenance applications.
- Non corrosive.
- Safe pH level (pH 9).
- High flashpoint (56°C) AIII.
- Environmentally compliant and fully biodegradable.



FlintGroup

Varn® Enviroflex Solvwash

Features	Benefits
<ul style="list-style-type: none"> Environmentally friendly formula. 	<ul style="list-style-type: none"> Ease of handling and disposal.
<ul style="list-style-type: none"> Dramatically reduces cleaning time. 	<ul style="list-style-type: none"> Quicker wash up times resulting in less down time.
<ul style="list-style-type: none"> pH well within industry standards. 	<ul style="list-style-type: none"> No erosion/corrosion to critical parts of the press surface.
<ul style="list-style-type: none"> Ensures anilox roller cells & gravure cylinders are 100% clean. 	<ul style="list-style-type: none"> Standardised ink film thickness and print quality.

Application	Aqueous Based Ink	Solvent Based Ink	UV Ink
Anilox Rollers	–	✓	–
Ink Metering Systems	–	✓	–
Impression Cylinders	–	✓	–
Press Frames	–	–	–
Nip Rollers	–	–	–
Path Rollers	–	–	–
Rewind Drums	–	–	–
Ancillary Cleaning Equipment	–	✓	–
Printing Plates	–	–	–

Product code

KV60-0UHG-#### (final 4 digits relate to pack size).

Pack sizes

1 litre (DKAF), 10 litres (DKF9), 20 litres (DKH5) and 200 litres (DKMP).

Application

Varn® Enviroflex Solvwash should be used undiluted.
 Apply Varn® Enviroflex Solvwash with a sponge, cloth, brush, pad or sprayer.
 Allow Varn® Enviroflex Solvwash to remain for a few minutes.
 Scrub the affected area (the Varn® Enviroflex Pad is recommended for optimum performance).
 Wipe away any residue and flush the surface with water or remove with a clean cloth.

Varn® Enviroflex Solvwash can be pumped or circulated through entire ink metering systems.

For optimum performance, use in conjunction with the Varn® Enviroflex Pad.

More products. Streamlined access. Greater results.

Flint Group's Print Media division offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks and Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

Print Media Europe
 Varn House, Brinell Drive,
 Northbank Industrial Park, Irlam,
 Greater Manchester, M44 5BL, UK.

T +44 (0)161 775 5412
F +44 (0)161 775 5415
printmedia.eu@flintgrp.com
www.flintgrp.com

The aim of our technical documents is to inform our customers about general values. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that this advice document cannot be used as the basis for claims in law. Furthermore, the correct application for each product has to be checked carefully for suitability.

Product names followed by ® are trademarks registered by Flint Group Incorporated.