

SCHWEGO® dur 8293

Cleaning paste for metal surfaces

Function:	Ink residues, lint, flash rust etc. will stick to bright machine parts during the printing process. In most cases, impression cylinders, angle bars, folder formers and parts of finishing machines or similar units are concerned. SCHWEGO [®] dur 8293 will clean the surface gently and intensively and will form a protective film against renewed soiling.
Properties:	 Intensive and gentle cleaning at the same time Economical in use Protection against flash rust Formation of a long-term protective layer
Application:	SCHWEGO[®] dur 8293 is applied with a rag. Clean the area to be treated with circular movements. Then wipe again with a dry rag.
Тір:	Subject to appropriate storage, the described properties of SCHWEGO [®] dur 8293 remain stable for at least 24 months.
Packaging:	250 g tube

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary. Further safety instructions please learn from our material safety data sheet. 08/2012

Bernd Schwegmann GmbH & Co. KG · Wernher-von-Braun-Str. 14 · 53501 Grafschaft-Gelsdorf · Germany Tel.: +49 (0) 2225 9226-0 · Fax +49 (0) 2225 9226-33 · E-Mail: info@SchwegmannNet.de · www.SchwegmannNet.de